



**Part #: 6500
Oil Cooler Kit**



Installers are encouraged to read instructions in their entirety before attempting installation.

WARNING: To reduce the risk of injury allow bike to cool before attempting installation.

Kit Content (quantity):

- | | |
|--------------------------|------------------------|
| Oil Cooler Assembly (1) | Oil hose (24") |
| Female flare fitting (1) | Male flare fitting (1) |
| Cable/zip tie (2) | 7/8" hose clamp (4) |
| Frame clamps (2) | Clamp shims (2) |
| 3/8" clamp bolts (2) | 3/8" nuts (2) |

Installation Tools:

- Flathead Screwdriver or 1/4" nut driver
- Sharp utility knife or utility scissor
- Small adjustable wrench(s)
- 5/16 Allen key

Installation Instructions:

1. Using supplied rubber shims, install frame clamps on right and left frame tubes in front of the steering shaft (Photo 1).



Photo 1.

2. Attach oil cooler assembly to frame clamps using supplied 3/8" nuts and bolts with the oil cooler nipples facing toward the motor.
3. Fasten clamp bolts firmly.
4. Remove the oil return line from the top of the oil tank. Replace with the supplied female flare fitting (Photo 2). Tighten firmly until stops.
5. Install the supplied male flare fitting into the female fitting removed from on oil tank in step 4 (Photo 2). Tighten firmly until stops.



Photo 2.

6. Cut supplied oil hose into two equal lengths.
7. Attach each of the equal length hoses to the oil cooler adapter nipples using the supplied hose clamps (Photo 3.)



Photo 3.

8. Loosely route oil lines from oil cooler and install oil lines onto the nipples of the male and female flare fittings installed in steps 4 and 5 using 7/8" hose clamps and fasten securely.

CAUTION: When routing oil hose avoid sharp bends that may kink and restrict oil flow.

ATTENTION: Only tighten hose clamps until snug. Over tightening will cut into rubber hose and result in oil leak.

1. Refill motor oil per owner's manual adding extra 10 fluid oz when installing the Jagg 10-row oil cooler.
2. Start vehicle and check for leaks.

Manufactured & Marketed by:

Setrab USA, Inc.

Johnstown, OH 43031

Tel. (740) 967-1726 • Fax. (740) 967-1749

www.jagg.com